

HMK 232 is a solvent-free, water-based impregnator that reduces the penetration of oil, water and dirt on soft and hard natural and artificial stone surfaces, terracotta, clay surfaces and unglazed tiles. Especially good for use on highly absorbent honed and textured surfaces. pH 9.5

APPLICATIONS

All natural and artificial stone surfaces. Ideal for pantry and galley areas.

EQUIPMENT

- Soft bristle brush, roller or lint-free cloths
- Gloves to protect your hands



Product **ISTHK050**
Size 1 L

INSTRUCTIONS

Before Applying Impregnator

- Check suitability with a test in an inconspicuous area. Follow the instructions on the label
- If underfloor heating exists, switch it off and allow the surface to cool to room temperature
- Clean the surface thoroughly before treatment. Rinse to remove any residue of cleaning chemicals
- Wait at least 24 hours before applying the impregnator. The stone must be completely dry before sealing

Step 1

- Shake bottle well before use
- Apply solution generously and evenly to the dry surface using a brush, roller or lint-free cloth
- Work on small areas at a time

Step 2

- On highly absorbent stones, repeat application after 1-2 hours. Subsequent applications should only be done using a natural hair bristle brush

Step 3

- Once the surface is dry you can remove any excess film with a damp cloth. Allow the surface to air-dry

TIPS

- Do not walk on treated surface until 8-12 hours after treatment has been completed
- Protect the surface from rain and humidity for 12 hours
- Resistance to oil and water is developed over 48 hours
- ⚠ Marble and limestone will remain sensitive to acids

TO ORDER

Shop online www.eyservices.com

Call +33 (0)4 89 02 43 40

Email info@eyservices.com

Whilst every effort has been made to ensure the accuracy of the information supplied herein, Earthly Supply Company cannot be held responsible or liable for any damage or injury arising from the use or misuse of these products.